


Technical Data:




# ZetaView<sup>®</sup> MONO


Technical Data




Subpopulations




Size




Fluorescence



Zeta Potential



Concentration



Colocalization



[www.particle-metrix.com](http://www.particle-metrix.com)

# Technical Data: PMX-130 ZetaView Mono Laser



## General Features

Measurement Principle	<ul style="list-style-type: none"><li>• Precision-engineered motorized scanning Nanoparticle Tracking Analysis (NTA) instrument for tracking the movement of individual visualized nanoparticles in suspension</li><li>• Real-time visualization of Brownian Motion and Electrophoretic Mobility, for measuring size, concentration and zeta potential in scatter and fluorescence mode*</li><li>• One software-controlled laser for enhanced fluorescence measurements*</li><li>• Software controlled 11-position fluorescence emission filter wheel for quick changes between scatter and fluorescence measurements as well as between different emission filters*</li><li>• Fast scanning to acquire and analyze typically more than 2000 particles in less than one minute</li><li>• Two software-controlled pumps for liquid transport and sample dosing</li></ul>
Samples	<ul style="list-style-type: none"><li>• Nanoparticles suspended in polar liquids and organic solvents (e.g. water, biological buffers, alcohols) for size, concentration, fluorescence and zeta potential studies*</li></ul>

## Hardware

Equipment	<ul style="list-style-type: none"><li>• ZetaView® PMX-130 main unit is equipped with a fixed NTA cell assembly, laser (see section Lasers) and bottles for buffer rinse</li><li>• Two software-controlled pumps for liquid transport and sample dosing</li><li>• Power of statistics by automated unique scan and dose control for measurement of 1 - 100 independent sub volumes</li><li>• Zeta potential option*</li><li>• fluorescence option features short acquisition times to avoid negative effect of photo bleaching*</li></ul>
Optical Layout	<ul style="list-style-type: none"><li>• 90° laser scattering video microscope with x10 magnification for maximized sample volume and highest statistics</li><li>• Automated alignment and focusing of laser and microscope</li></ul>
Camera	<ul style="list-style-type: none"><li>• High sensitive CMOS camera 640 x 480 pixels</li><li>• Variable frame rate from 2 to 60 Hz for optimum resolution and fast acquisition</li></ul>
Lasers	<ul style="list-style-type: none"><li>• Available laser wavelengths: 405 nm, 488 nm, 520 nm, 640 nm, and 660 nm at typical laser power of &gt;30 mW</li><li>• Pulse duration 0.1 ms up to continuous</li></ul>
Fluorescence	<ul style="list-style-type: none"><li>• Long wave-pass (LWP) cut-off filters: @405 nm: 430 nm @488 nm: 500 nm @520 nm: 550 nm @640 nm: 680 nm @660 nm: 680 nm</li><li>• Customized LWP and bandpass filter available on request</li></ul>
Cleaning	<ul style="list-style-type: none"><li>• Tool-free access to glass cuvette for quick and simple cleaning process</li><li>• Cell cleaning recommended weekly or monthly depending on sample type and usage</li><li>• Cleaning of driver electrodes required after &gt;1000 zeta potential runs*</li><li>• Cleaning kit and spare parts included in delivery</li></ul>
Temperature Range/Control	<ul style="list-style-type: none"><li>• External working temperature range: 5°C to 45°C</li><li>• Sample temperature control: Peltier temperature control from RTP -5°C to 55°C with automated dew-point sensing</li></ul>

\* With zeta potential option



# Technical Data: PMX-130 ZetaView Mono Laser



## Computer System

Control Device	<ul style="list-style-type: none"> <li>• Intel® NUC Mini PC</li> <li>• 500 GB SSD hard drive</li> <li>• Windows 10 Professional</li> <li>• Maclean holder for mounting computer at backside of screen</li> <li>• Keyboard and mouse</li> </ul>
Monitor	<ul style="list-style-type: none"> <li>• 24" LED screen (or better)</li> </ul>

## Software

Communication	<ul style="list-style-type: none"> <li>• Software provided on pre-configured PC, communication via Ethernet</li> </ul>
Quality Control	<ul style="list-style-type: none"> <li>• Cell quality check, daily performance check, outlier control with automatic Grubbs statistical analysis of measurement data</li> </ul>
Live Monitoring	<ul style="list-style-type: none"> <li>• Number of detected particles in scatter and fluorescence mode*, scattering intensity, conductivity*, temperature, particle drift</li> </ul>
Standard Operating Procedures (SOP)	<ul style="list-style-type: none"> <li>• Fully-customizable SOPs for different samples/applications</li> </ul>
Analysis and Reports	<ul style="list-style-type: none"> <li>• Data Analysis: particle size distribution profiles, concentrations, overlays and averaging, scatter plots, zeta potential distribution profiles, sub-population analysis (using additional 'Particle Explorer' software)</li> <li>• Data export format: AVI, TXT, CSV, FCS, PDF reports containing key results</li> </ul>

## Measurement Specifications

Size/Concentration	<ul style="list-style-type: none"> <li>• Concentration range: 105 – 109 particles/ml</li> <li>• Particle size: 10nm – 1000nm (dependent on sample and laser selection)</li> <li>• Accuracy: ±5nm (for 100nm polystyrene latex)</li> <li>• Reproducibility: ±2nm (for 100nm polystyrene latex)</li> </ul>
Fluorescence	<ul style="list-style-type: none"> <li>• Concentration range: 105 – 109 particles/ml</li> <li>• Particle size: 20nm – 1000nm (dependent on fluorescent dye and laser selection)</li> <li>• Accuracy: ±5nm (for 100nm polystyrene latex)</li> <li>• Reproducibility: ±2nm (for 100nm polystyrene latex)</li> </ul>
Zeta Potential*	<ul style="list-style-type: none"> <li>• Working range: -500 to +500mV</li> <li>• Concentration range: 106 – 1010 particles/ml</li> <li>• Particle size: 20nm – 5000nm (dependent on sample and laser selection)</li> <li>• Conductivity range: 3µS/cm – 15mS/cm</li> <li>• Accuracy: ±4mV (zeta potential standard)</li> <li>• Reproducibility: ±2mV (zeta potential standard)</li> </ul>
General	<ul style="list-style-type: none"> <li>• Minimum sample quantity: 500µl of sample at 105 particles/ml</li> <li>• pH range: 1 – 13</li> <li>• Temperature: 5°C to 45°C (external temperature)</li> <li>• Sample volume visualised and tracked by the camera for a single measurement: 11 x 3.3 nL</li> </ul>
Reference Materials	<ul style="list-style-type: none"> <li>• Nominal 100 nm reference suspension for size</li> <li>• Nominal 100 or 200 nm reference suspension for fluorescence*</li> <li>• Nominal -50mV reference suspension for zeta potential*</li> </ul>

\* With zeta potential option,



# Technical Data: PMX-130 ZetaView Mono Laser



## Dimensions

Physical	<ul style="list-style-type: none"><li>• Footprint (W x D x H): 20 x 30 x 25cm</li><li>• Weight: 8.5kg (main unit, PC and monitor extra)</li><li>• Shipping box with standard content:<ul style="list-style-type: none"><li>Main unit: 62 x 51 x 47cm; 16,7 kg to 18,5 kg*</li><li>Minimum 24" Monitor: 67 x 19 x 39cm; 6,12 kg</li></ul></li></ul>
Electrical	<ul style="list-style-type: none"><li>• 90-240V, 47-63Hz, 50VA</li></ul>

## Warranty & Support

Warranty	<ul style="list-style-type: none"><li>• 1 year (glass excluded)</li></ul>
Service & Support	<ul style="list-style-type: none"><li>• Reaction time: 48 hours</li><li>• Maintenance, service and IQ/OQ contracts can be purchased on request</li><li>• Support via telephone, e-mail and remote desktop software</li><li>• software for trained users free of charge during warranty period</li><li>• Training courses for new users available on demand</li><li>• Special arrangements and specifications can be purchased on request – quotation required</li></ul>

### Head Office

**Particle Metrix GmbH**  
Wildmoos 4  
D-82266 Inning / Germany  
  
+49-8143-99172-0  
info@particle-metrix.de

### US Office

**Particle Metrix Inc.**  
Mebane, NC 27302 / USA  
  
+1-919-667-6960  
usa@particle-metrix.com

### Worldwide Distributors



**Innovation paired with cooperative spirit**

\* With zeta potential option

V2023\_01



[www.particle-metrix.com](http://www.particle-metrix.com)